



4000[®] SUBFLOOR

CONSTRUCTION ADHESIVE



**HIGH
STRENGTH**
**WEATHERPROOF
BOND**

DAP[®] 4000[®] SUBFLOOR Construction Adhesive

is a premium grade solvent construction adhesive specifically formulated for subfloor and deck installation. Using this easy-to-gun, solvent-based adhesive during the installation process prevents floor squeaks and improves the structural performance of the floor assembly.

SOLVENT FORMULA

**BONDS WET, FROZEN
& TREATED LUMBER**

**MEETS / EXCEEDS
ASTM D3498**

**PREVENTS
FLOOR SQUEAKS**



4000[®] SUBFLOOR

**SOLVENT
FORMULA**


SUBFLOOR • WOOD-TO-WOOD ASSEMBLIES • GLUED FLOOR SYSTEMS • DECK INSTALLATION



**HIGH
STRENGTH**
**WEATHERPROOF
BOND**

PREVENTS FLOOR SQUEAKS & IMPROVES STRUCTURAL PERFORMANCE

MULTI-MATERIAL ADHESION




Plywood

OSB

Enhanced
OSB

Metal

Masonry



Concrete

Wood

Treated
Lumber

Dimensional
Lumber



WET



FROZEN



TREATED

- Bonds Wet, Frozen & Treated Lumber
- Meets / Exceeds ASTM D3498

FEATURES & BENEFITS

- Water-Resistant
- Application Temperature Range:
0°F - 120°F
- Service Temperature Range:
-20°F - 140°F
- 15 Minute Working Time
- Interior / Exterior

COVERAGE

28 FL OZ

1/4" bead yields 86 linear feet

3/8" bead yields 38 linear feet

DESCRIPTION	SIZE	CASE PACK / PALLET	PRODUCT CODE	GTIN14	CASE WEIGHT (LB)	CASE DIMS (LXWXH)	CASE VOL (CU FT)
4000 [®] SUBFLOOR	28 FL OZ	12 / 60	0 70798 25117 5	100 70798 25117 2	28	10.875" X 8.25" X 17.125"	0.89