



THE SPEC LINE

WHAT THE JOB DEMANDS.SM

800

Premium Polymer Sealant

Meets AAMA 800

WHAT'S YOUR JOB?

- WINDOWS
- DOORS
- SIDING
- TRIM

THE SPECIFICATION

Meets AAMA 800
*(803 & 804 Specification
voluntary specifications and
test methods for sealants)

THE PRODUCT

DAP® DYNAFLEX™ 800 Premium Polymer Sealant provides a watertight, weatherproof seal. Can be used to install & seal around windows, doors & penetrations where a tough durable seal is required.

Ideal for sealing dissimilar substrates & has excellent adhesion to most common building materials.

- Ideal window flange sealant
- No shrinkage
- Adheres to wet and damp surfaces



*803 Narrow joint seam sealers for use with fenestration products
803.3 Exterior perimeter sealing compound



THE SPEC LINE
WHAT THE JOB DEMANDS.SM

800

Premium Polymer Sealant
Meets AAMA 800

LIMITED WARRANTY: DAP Products Inc. warrants that this product, when applied in accordance with DAP's label, technical bulletins and applicable industry standards, will be free from defects in material for 12 months from the date of purchase, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond DAP's control and could affect performance, DAP makes no other warranties, express or implied, including the warranties of **Merchantability or Fitness for a Particular Use or Purpose**. If a product defect is encountered, call 1-888-DAP-TIPS for warranty fulfillment. You must have your sales receipt and product container available when you call. DAP's sole liability is either to supply replacement product or refund the purchase price. DAP will in no event be liable for incidental or consequential damages.

QUESTIONS? Call 1-888-DAP-Tips or visit dap.com & Click on "ASK the Expert"

Performance Facts

Amount per Cartridge: 300 mL (10.1 fl. oz.)
Recommended Bead: 1/4" to 3/8"
Coverage per Cartridge: 1/4" bead, 31 lin. ft.
 3/8" bead, 14 lin. ft.

Recommended Use: Interior & exterior window & door installation & weatherization sealing applications. Compatible with butyl & asphalt flashing.

Not Recommended For: Below waterline or below grade applications; joints exceeding 1/2" wide by 1/2" deep; window glazing.

Features: Adheres to Wet Surfaces • Extreme Flexibility • Applies at Temperatures as Low as 20°F • Low Odor • Paintable • Low VOC • Cured Sealant is Mold & Mildew Resistant • Excellent UV Resistance

Adheres To: Vinyl • Aluminum • Metal • Fiber Cement • Masonry • Wood • Most Common Building Materials

SPECIFICATIONS:

AAMA 800 Meets or Exceeds
ASTM C920 Meets or Exceeds

PHYSICAL PROPERTIES:

VOC Content: CA ARB <3% wt./wt. (CCSC)
Solids: 99.9% by weight
Application Range: 20°F to 120°F
Shelf Life: 12 months
Skin Time: 45 minutes
Cure Time: 24 hours

Uncured Sealant Clean-Up: Mineral Spirits
Cured Sealant Clean-Up: Cut or Scrape
Will Not Freeze

Case Code	Size	Color	Product Code	Case Weight Weight	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
80800	10.1 OZ	WHITE	80800	13	12	8x6x12.5	0.3	3	108