



# DYNAFLEX<sup>®</sup> 920

## SPEC LINE

WINDOW, DOOR & SIDING SEALANTS



**MEETS ASTM C920  
CLASS 25**

**DAP<sup>®</sup> DYNAFLEX<sup>®</sup> 920 PREMIUM EXTERIOR ELASTOMERIC SEALANT** is a high performance sealant developed for professional window, door, siding and trim installations. It provides a long-lasting elastomeric seal which helps prevent water and air intrusion. An extensive offering of colors provides an aesthetically appealing finished look to any installation. Can be applied in most weather conditions and will not wash away when exposed to rain prior to full cure.

**APPLIES IN TEMPERATURES  
AS LOW AS 20°F**

**PERMANENTLY FLEXIBLE  
& CRACKPROOF**

**ADHERES TO WET  
& DAMP SURFACES**



TECHNICAL  
SPECIFICATIONS



**AVAILABLE IN:**

200+ LEADING WINDOW, DOOR & SIDING COLORS

# DYNAFLEX<sup>®</sup> 920

PREMIUM EXTERIOR ELASTOMERIC SEALANT



## SUPERIOR FLEXIBILITY & ADHESION

- No Cracking, Extremely Flexible**  
Stays flexible to withstand extreme joint expansion.
- Immediately Rain Ready**  
Provides 100% waterproof & weatherproof seal.
- Extreme Temperature Application**  
Excellent UV resistance.
- Self-Tooling & VOC Compliant**  
Guns out easily & tools smoothly.
- Paintable After Cure**  
Cured sealant is mold & mildew resistant.
- 4" Nozzle for Easy Application**
- Exterior**

## MATCHES LEADING WINDOW, DOOR, SIDING & TRIM COLORS



PERFORMANCE FEATURE	DYNAFLEX 920	COMPETITOR A	COMPETITOR B
PEEL ADHESION (ASTM C794) ALUMINUM	19.8 LBF	8.5 LBF	10.2 LBF
PEEL ADHESION (ASTM C794) VINYL	15.0 LBF	9.8 LBF	10.8 LBF
PEEL ADHESION (ASTM C794) SMARTSIDE <sup>®</sup>	22.8 LBF	9.1 LBF	12.4 LBF
JOINT MOVEMENT (ASTM C719) ALUMINUM	PASS	PASS	PASS
JOINT MOVEMENT (ASTM C719) GLASS	PASS	PASS	FAIL
JOINT MOVEMENT (ASTM C719) MORTAR	PASS	FAIL	FAIL
EXTRUSION (HOT – 100°F) PEAK LOAD	69.35 LBS	77.82 LBS	64.25 LBS
EXTRUSION (COLD – 32°F) PEAK LOAD	209.2 LBS	298.8 LBS	170.1 LBS
LAP SHEAR (14 DAYS)	46.25 PSI	14.17 PSI	14.52 PSI

### COLOR MATCH TOOL:



Use the DAP Color Match tool to identify the best color match for your project. Dynaflex 920 is produced in colors that match leading siding, window & coil manufacturer's colors.

### IDEAL FOR SEALING:

- Windows
- Doors
- Siding
- Exterior Trim
- Gutters
- Flashing
- Pipes
- Vents
- Ducts

### EXCELLENT ADHESION TO

- Wood
- Vinyl
- Most Plastics
- Aluminum
- Most Metals
- Fiber Cement
- Concrete
- Mortar
- Brick
- Stone
- Glass
- Ceramic
- Fiberglass
- Stucco
- Most Building Materials

DESCRIPTION	COLOR CODE	SIZE	CASE PACK / PALLET	PRODUCT CODE	GTIN14	CASE WEIGHT (LB)	CASE DIMS (LXWXH)	CASE VOL (CU FT)
WHITE	WT098	10 FL OZ	12 / 132	0 70798 89200 2	100 70798 89200 9	13.00	8" X 6" X 12.5"	0.35

FOLLOW COLOR MATCH TOOL QR CODE ABOVE FOR ALL DYNAFLEX 920 COLOR SPECIFICATION INFORMATION