



DAP® SMARTBOND SUBFLOOR Foam Construction

**Adhesive** is a high strength polyurethane foam adhesive that is fast and easy to use. A single can provides 8X the coverage of a subfloor cartridge adhesive. The unique technology applies as a foam and transforms by collapsing into a high-strength, fast-curing adhesive gel that bonds to wet, dry, frozen and treated lumber. An easy-to-use screw top threads onto an applicator gun providing precise bead control for high volume subfloor applications.

HIGH STRENGTH BOND

COLLAPSING FOAM ADHESIVE

BONDS DRY, WET & FROZEN LUMBER



COVERAGE\* MIGER! EXTREMELY FLAMMABLE.

MINE MAY CAUSE FLASH FIRE. CONTENTS UNDER

MINISTRAL REGISTRAL REGI PLIEROI: LINITANT. Read back panel carefully for causus CHEROI: EXTREMADAMENTE INFLAMABLE. LOS VAPORES PLEI UNA COMBUSTION ESPONTÁNEA. CONTENIDO BAJO PRESOI. RIMATE Las atentamente otras precauciones en el panel del revesa.

NET WT. 20 OZ (567 g)



SUBFLOOR INSTALLATIONS • DECKING INSTALLATIONS



MORE COVERAGE\*



- FASTER & EASIER APPLICATION THAN TRADITIONAL CARTRIDGES
- DURABLE, HIGH-STRENGTH BOND

COMPATIBLE WITH ALL DAP® SHARPSHOOTER APPLICATORS INCLUDING 44" SHARPSHOOTER XXL

REDUCES REACHING, BENDING OVER & WALKING ON JOISTS

## PRODUCT DETAILS

**Application Temperature:** 25°F - 120°F

**Service Temperature:** -40°F - 195°F

Working Time: 20 Minutes Full Cure Time: 24 Hours

Coverage: ½" Bead Yields Up to 400 Linear Feet

Shelf Life: 18 Months

**VOC Compliant** 

Interior/Exterior

## POWERFUL ADHESION TO:



Lumber

Metal

**OSB** 

Plywood



BONDS WET, FROZEN & TREATED LUMBER

rage Comparison: SmartBond Subfloor applied at 1/2" bead versus DAP subfloor cartridge adhesi

DESCRIPTION	SIZE	CASE PACK / PALLET	PRODUCT CODE	GTIN14	CASE WEIGHT (LB)	CASE DIMS (LXWXH)	CASE VOL (CU FT)
SMARTBOND SUBFLOOR	20 OZ	6 / 128	0 70798 00054 4	100 70798 00056 5	10.20	8.5" X 5.75" X 11.5"	0.325