# 3750 Multi Slide System







## 3750 Multi Slide System

### **Features and Benefits**

#### Sizing

- Standard sizing in 9',12',and 15' x 8' in 3 panel Configuration.
- Standard sizing in 12',16',and 20' x 8' in 4 panel Configuration.
- Maximum panel size is 5'x 8' or 40 sq ft.
- Maximum frame width of 3 panel door system at 15'.
- Maximum width of 4 panel door system at 20'.
- · Custom sizing available.

#### ■ Frame

- KD or welded main frame.
- 7¾" total width 6¾"jamb depth all PVC multi-chambered profile frame system (on 3 panel).
- 10¾6" total width 9¾6" jamb depth all PVC multi-chambered profile frame system (on 4 panel).
- Integrated nail fin application with 1"or 1%" set back.
- Full length weather stripping on all 4 frame components.
- Integrated sill drainage with snap-in sill covers.

#### Sash

- Fully welded vinyl sash with internal aluminum reinforcement with 1/8" standard IG, or a 11/4" triple insulated glass system.
- Many high energy-efficient glass options for the most extreme temperature sensitive regions.
- Standard glazing, Cardinal™ LoE 366® dual glazed tempered glass.
- All stiles are metal reinforced for extreme wind load resistance.
- Unique internal drainage system to minimize risk of seal failures.
- Interior glazed for better performance.

#### Hardware

- Truth Nexus 2 point lock with opposing lock points.
- Anti-lock feature preventing a "false" sense of lock up.
- Flush mount handle does not protrude into the room.
- Deep finger pocket provides superior grip area for moving large door panels.
- Recessed thumb slide intuitive locking and unlocking of panel.
- Stainless steel roller housing and composite wheels with side adjustment, AAMA rated to carry a 500 pound panel for 10,000 cycles without change to adjustment.
- Hardware colors; white, black powder coat, and brushed chrome.

#### Extruded Vinyl Colors



Beige

**Optional Exterior Coated** Stocked Colors







#### Optional

Black Interior and Exterior Specialty Laminate









